

# Chapter 9

## DTD for ARP Response Tags

This chapter contains the document type definition (DTD) called `junos-arp.dtd`, which lists the tags returned by the JUNOScript server to describe ARP information. The associated Extensible Markup Language (XML) namespace is `http://xml.juniper.net/junos/5.6R1/junos-arp`. To review reference pages for the tags, see “Summary of ARP Response Tags” on page 96.

```
<!-- Copyright (c) 2000-2002, Juniper Networks, Inc. -->  
<!-- All rights reserved. -->  
<!-- junos-arp.dtd -->
```

```
<!ELEMENT arp-entry-count (#PCDATA)>
```

```
<!ELEMENT arp-table-entry (mac-address | ip-address | hostname | interface-name |  
arp-table-entry-flags)*>
```

```
<!ELEMENT arp-table-entry-flags (none | permanent | published | dead | free)*>
```

```
<!ELEMENT arp-table-information (arp-table-entry | arp-entry-count)*>  
<!ATTLIST arp-table-information junos:style CDATA #IMPLIED>
```

```
<!ELEMENT clear-arp-table-result (ip-address | clear-success)*>
```

```
<!ELEMENT clear-arp-table-results (clear-arp-table-result)*>
```

```
<!ELEMENT clear-success EMPTY>
```

```
<!ELEMENT dead EMPTY>
```

```
<!ELEMENT free EMPTY>
```

```
<!ELEMENT hostname (#PCDATA)>
```

```
<!ELEMENT interface-name (#PCDATA)>
```

```
<!ELEMENT ip-address (#PCDATA)>
```

```
<!ELEMENT mac-address (#PCDATA)>
```

```
<!ELEMENT none EMPTY>
```

```
<!ELEMENT permanent EMPTY>
```

```
<!ELEMENT published EMPTY>
```

